

# Socket Set

3054MR

3/8"

Blow case size (mm) :  
340 x 263 x 80 (0.25cuft)

Contents



3.85



1 / 3

|  |  |          |                                                        |
|--|--|----------|--------------------------------------------------------|
|  |  | 3330M    | 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 17, 18, 19, 21, 22 |
|  |  | 3235M    | 8, 10, 12, 13, 14                                      |
|  |  | 1025T    | T10, T15, T20, T25, T30, T40, T45 T50                  |
|  |  | 3630     | 16, 21                                                 |
|  |  | 1145MR   | H1.5, H2, H2.5, H3, H4, H5, H6, H8, H10                |
|  |  | 14A1     | PH2 x 100                                              |
|  |  | 14A2     | 5.5 x 100                                              |
|  |  | 1060     | 8, 10, 12, 13, 14, 17, 19                              |
|  |  | 3771-08G | 3792                                                   |
|  |  |          | 3221-03<br>3221-06                                     |
|  |  | 314808S  | 6111-06                                                |



54  
PC.

3568MR

3/8"

Metal shelf size (mm) :  
415 x 336 x 320 (1.58 cuft)

Contents

Each Q'ty

|  |  |                         |                        |
|--|--|-------------------------|------------------------|
|  |  | 8, 9, 10, 11, 12, 13    | 10                     |
|  |  | 3335M                   | 14, 15, 16, 17, 18, 19 |
|  |  | 21, 22, 23, 24          | 6                      |
|  |  | 7, 8, 9, 10, 11, 12, 13 | 10                     |
|  |  | 3235M                   | 14, 15, 16, 17, 18, 19 |
|  |  | 21, 22, 24              | 6                      |



268  
PC.

| KT NO.   | Spec.                     | kg    | Cuft |
|----------|---------------------------|-------|------|
| 3568MR-A | 87102                     | 6.35  | 0.67 |
| 3568MR-D | 268 PC.<br>socket content | 16.50 | 0.38 |

