


Insert Tool

345022

• Chrome plated

▪ Square drive size : 14 x 18

KT NO.	Size mm	Maximum Torque N·m	Lw* mm	L mm		
34502213M	13	108	25	62.2	129	12 / 192
34502214M	14	128	25	63.2	128	12 / 192
34502215M	15	152	25	63.3	125	12 / 192
34502216M	16	175	25	63.1	137	12 / 192
34502217M	17	202	25	65.0	134	12 / 192
34502218M	18	230	25	65.0	134	10 / 160
34502219M	19	262	25	66.7	135	10 / 160
34502221M	21	330	25	67.3	151	10 / 160
34502222M	22	368	25	68.5	156	6 / 96
34502224M	24	452	25	69.9	156	6 / 96
34502227M	27	595	31	78.0	201	6 / 96
34502230M	30	762	31	79.6	198	6 / 96
34502232M	32	800	31	81.0	201	6 / 96
34502234M	34	800	31	82.4	225	6 / 90
34502236M	36	800	31	83.7	230	6 / 90
34502241M	41	800	31	86.6	235	6 / 90



KT NO.	Size inch	Maximum Torque N·m	Lw* mm	L mm		
34502216S	1/2	108	25	62.2	128	12 / 192
34502218S	9/16	128	25	63.2	128	12 / 192
34502220S	5/8	175	25	63.1	132	12 / 192
34502224S	3/4	262	25	66.7	141	10 / 160

Interchangeable Torque Wrench Set

34510

34520



KT NO.	 mm	Contents		
345102D08MR		34512-2DG 4~20 N·m		
345104D08MR		34512-4DG 10~60 N·m		
345101E08MR		34512-1EG 20~100 in·lb		
345102E08MR		34512-2EG 40~200 in·lb		
			34503102R 1/4" DR.	345011M 345021M
			34503103R 3/8" DR.	
			34503102R 1/4" DR.	10, 13, 17
			34503102R 1/4" DR.	10, 13, 17

KT NO.	 mm	Contents		
345202C11MR		34522-2CG 20~150 ft·lb 34~197 N·m		
345201D11MR		34522-1DG 20~100 N·m		
345202D11MR		34522-2DG 40~200 N·m		
345203D11MR		34522-3DG 60~340 N·m		
345201E11MR		34522-1EG 15~80 ft·lb		
345202E11MR		34522-2EG 20~150 ft·lb		
345203E11MR		34522-3EG 50~250 ft·lb		
			34503204R 1/2" DR.	345012M 13, 14, 15, 17, 19, 22, 24, 27, 30
			34503203R 3/8" DR.	
			34503204R 1/2" DR.	
			34503204R 1/2" DR.	
			34503203R 3/8" DR.	
			34503204R 1/2" DR.	
			34503204R 1/2" DR.	