

Circlip Pliers

• Grip material - PVC

66HS


66HB

66SS

66SB



- Design of hidden spring
- Straight and angled pattern
- High strength of tip
- DIN 5254, DIN 5256



Internal type



External type

KT NO.	Tips	Overall length inch mm	Ø-tips	Capacity Ø mm		
66HS-07		7 188	1.8	19~60	176	8 / 48
66HB-07		7 175	1.8	19~60	176	8 / 48
66SS-07		7 188	1.8	19~60	195	8 / 48
66SB-07		7 175	1.8	19~60	195	8 / 48

67HS

67HB

67SS

67SB

68HS

68HB



68SS

68SB



- For internal retaining rings
- Straight and angled pattern
- DIN 5254, DIN 5256



Internal type

- For external retaining rings
- Straight and angled pattern
- DIN 5254, DIN 5256




External type

Japanese type

European type

Japanese type

European type



KT NO.	Tips	Overall length inch mm	Ø tips	Capacity Ø mm		
67HS-07		7 180	1.8	19~60	129	12 / 144
67HB-07		7 180	1.8	19~60	131	12 / 144
68HS-05		5 125	1.3	12~28	83	10 / 80
68HS-07		7 180	1.8	19~60	134	12 / 144
68HS-10		10 250	2.3	40~100	322	8 / 64
68HB-05		5 125	1.3	12~28	94	10 / 80
68HB-07		6-3/4 170	1.8	19~60	131	12 / 144
68HB-10		9-1/2 241	2.3	40~100	317	6 / 48

KT NO.	Tips	Overall length inch mm	Ø tips	Capacity Ø mm		
67SS-07		7 180	1.8	19~60	151	12 / 144
67SB-07		7 180	1.8	19~60	150	12 / 144
68SS-05		5 125	1.3	12~28	97	10 / 80
68SS-07		7 180	1.8	19~60	154	12 / 144
68SS-10		10 250	2.3	40~100	323	8 / 64
68SB-05		5 125	1.3	12~28	96	10 / 80
68SB-07		6-3/4 170	1.8	19~60	152	12 / 144
68SB-10		9-1/2 241	2.3	40~100	316	6 / 48