


- Magnet
- Chrome plated with black tip

- Color rubber handle
- Grip material - PP + TPR



Go Thru Screwdriver & Set

KT No. & D1



- Shank material - SNCM - V alloy steel
- Grip material - PP + TPR
- Finishing - chrome plated with black tips

1461



- Phillips head, hex-shank
- DIN ISO 8764

KT NO.	No.	mm	inch	mm	mm	g	
14610103	PH1	75	3	5.0	10	121	12 / 96
14610204	PH2	100	4	6.0	10	135	12 / 96
14610206	PH2	150	6	6.0	10	148	12 / 144
14610306	PH3	150	6	8.0	13	219	12 / 96



1462



- Slotted head, hex-shank
- DIN ISO 2380

KT NO.	mm	inch	mm	mm	mm	g	
14625504	5.5	7/32	1.0	100	4	5.0	10 125 12 / 96
14626504	6.5	1/4	1.2	100	4	6.0	10 134 12 / 96
14626506	6.5	1/4	1.2	150	6	6.0	10 147 12 / 144
14620806	8.0	5/16	1.2	150	6	8.0	13 217 12 / 144
14620807	8.0	5/16	1.2	175	7	8.0	13 228 12 / 144
14621008	10.0	3/8	1.6	200	8	10.0	16 310 12 / 72
14621012	10.0	3/8	1.6	300	12	10.0	16 391 10 / 40
14621210	12.0	15/32	2.0	250	10	10.0	16 347 10 / 40



30206MR

Contents

1.20 1 / 20

1461 PH1 x 75, PH2 x 100, PH3 x 150

1462 5.5 x 100, 6.5 x 150, 8.0 x 175



6 PC.

35208MR

Blow case size (mm) :
430 x 300 x 50 (1.29 cuft)

Contents

2.16 1 / 4

1461 PH1 x 75, PH2 x 100, PH3 x 150

1462 6.5 x 100, 8.0 x 175, 10 x 300

1421 PH2 x 38

1422 6.5 x 38



8 PC.