


Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted
- Total length : 25 mm



Item No.xxxxxxx.B



order unit :one box

1025P

- DIN ISO 2351-2



KT NO.	⊕ No.	g	g	g
102500P (102500P.B)	PH0	5		
102501P (102501P.B)	PH1	5		
102502P (102502P.B)	PH2	6		
102503P (102503P.B)	PH3	6		
102504P (102504P.B)	PH4	6		
			20 / 300 (50 / 1000)	

102512P

- Reduced for dry-wall
- DIN ISO 2351-2



KT NO.	⊕ No.	g	g	g
102512P (102512P.B)	PH2	6		
			20 / 300 (50 / 1000)	

1025S

- DIN ISO 2351-1



KT NO.	Tip width (mm)	Tip thickness (mm)	g	g	g
102503S1 (102503S1.B)	3.0	0.5	5		
102535S1 (102535S1.B)	3.5	0.6	5		
102504S1 (102504S1.B)	4.0	0.5	5		
102504S2 (102504S2.B)	4.0	0.8	5		
102545S1 (102545S1.B)	4.5	0.6	5		
102505S1 (102505S1.B)	5.0	0.8	5		
102555S1 (102555S1.B)	5.5	0.8	5		
102555S2 (102555S2.B)	5.5	1.0	5		
102506S1 (102506S1.B)	6.0	1.0	5		
102565S1 (102565S1.B)	6.5	1.2	6		
102507S1 (102507S1.B)	7.0	1.2	6		
102508S1 (102508S1.B)	8.0	1.2	6		
102508S2 (102508S2.B)	8.0	1.6	6		
			20 / 300 (50 / 1000)		

1025H

- DIN ISO 2351-3



KT NO.	mm	g	g	g
102515H (102515H.B)	H1.5	4		
102502H (102502H.B)	H2	5		
102525H (102525H.B)	H2.5	5		
102503H (102503H.B)	H3	5		
102504H (102504H.B)	H4	6		
102505H (102505H.B)	H5	6		
102506H (102506H.B)	H6	6		
102507H (102507H.B)	H7	8		
102508H (102508H.B)	H8	9		
102510H (102510H.B)	H10	12		
			20 / 300 (50 / 1000)	

KT NO.	inch	g	g	g
502503H (502503H.B)	3/64	4		
502504H (502504H.B)	1/16	4		
502505H (502505H.B)	5/64	5		
502506H (502506H.B)	3/32	5		
502507H (502507H.B)	7/64	5		
502508H (502508H.B)	1/8	5		
502509H (502509H.B)	9/64	5		
502510H (502510H.B)	5/32	5		
			20 / 300 (50 / 1000)	

1025T

- For torx head screw



KT NO.	Size	g	g	g
102506T (102506T.B)	T6	5		
102507T (102507T.B)	T7	5		
102508T (102508T.B)	T8	5		
102509T (102509T.B)	T9	5		
102510T (102510T.B)	T10	5		
102515T (102515T.B)	T15	5		
102520T (102520T.B)	T20	5		
102525T (102525T.B)	T25	5		
102527T (102527T.B)	T27	5		
102530T (102530T.B)	T30	5		
102535T (102535T.B)	T35	6		
102540T (102540T.B)	T40	6		
102545T (102545T.B)	T45	7		
102550T (102550T.B)	T50	8		
			20 / 300 (50 / 1000)	

1025U

- For torx head screw
- Tamper-resistant type



KT NO.	Size	g	g	g
102507U (102507U.B)	T7H	4		
102508U (102508U.B)	T8H	5		
102509U (102509U.B)	T9H	5		
102510U (102510U.B)	T10H	5		
102515U (102515U.B)	T15H	5		
102520U (102520U.B)	T20H	5		
102525U (102525U.B)	T25H	5		
102527U (102527U.B)	T27H	5		
102530U (102530U.B)	T30H	6		
102540U (102540U.B)	T40H	6		
			20 / 300 (50 / 1000)	

1025M

- DIN 65254



KT NO.	size	g	g	g
102504M	M4	5		
102505M	M5	5		
102506M	M6	6		
102508M	M8	7		
102510M	M10	10		
			20 / 300	

1025V

- For inside 5-star screw
- Tamper-resistant type



KT NO.	Size	g	g	g
102508V	IPR 8	5		
102509V	IPR 9	5		
102510V	IPR 10	5		
102515V	IPR 15	5		
102520V	IPR 20	5		
102525V	IPR 25	5		
102527V	IPR 27	5		
102530V	IPR 30	5		
102540V	IPR 40	6		
			20 / 300	

