

T - type Wrench & Set

KT No. & D1



- Material - SNCM - V alloy steel
- Finishing - chrome plated with black tip

1153R



- For torx head screw



11A3R



- For torx head screw



KT NO.	Size	mm	mm	mm	g	kg
115310R	T10	100	137	90	40	10 / 200
115315R	T15	100	137	90	40	10 / 200
115320R	T20	100	137	90	40	10 / 200
115325R	T25	100	137	90	40	10 / 200
115327R	T27	150	188	100	73	10 / 200
115330R	T30	150	188	100	74	10 / 200
115340R	T40	150	188	100	88	10 / 200
115345R	T45	200	240	120	173	10 / 120
115350R	T50	200	240	120	173	10 / 120

KT NO.	Size	mm	mm	mm	g	kg
11A310R	T10	200	237	90	53	12 / 192
11A315R	T15	200	237	90	53	12 / 192
11A320R	T20	200	237	90	53	12 / 192
11A325R	T25	200	237	90	53	12 / 192
11A327R	T27	200	238	100	86	10 / 160
11A330R	T30	200	238	100	86	10 / 160
11A340R	T40	200	238	100	105	10 / 160



KT NO.	PC.	Spec	Contents	kg	kg
21108MR	8	Ball hex type	1150MR H2, H2.5, H3, H4, H5, H6, H8, H10	1.10	1 / 12
21208MR	8	Hexagon type	1155MR H2, H2.5, H3, H4, H5, H6, H8, H10	1.10	1 / 12
21208SR	8		1155SR 5/64, 3/32, 1/8, 5/32, 3/16, 1/4, 5/16, 3/8	1.10	1 / 12
21309PR	9	torx head type	1153R T10, T15, T20, T25, T27, T30, T40, T45, T50	1.20	1 / 12

23208MR



8 PC.

- Perfect for when you need more leverage than a standard hex, or space is limited and you can't get a good swing on a standard wrench
- Spring and ball detent to secure the Sliding T
- It turns fasteners quickly and continuously with free spinning collar



- Speed & Efficiency
- Locking Stopper
- Extension



KT NO.	PC.	Spec	Contents	kg	kg
23208MR	8	Hexagon type 1195AM	H2, H2.5, H3, H4, H5, H6, H8, H10	1.64	1 / 6

