- Used to remove the crankshaft pulley when replacing the timing belt
- The pulley retaining bolt is fitted with high torque and the flywheel must be securely locked during installation
- Jamming tools into the teeth of the flywheel will cause serious damage to both teeth and housing











Petrol 1.6 16v. Twin Cams (Belt)

MODEL:


Stilo

## **FIAT**

# Petrol Engine Flywheel Holding Tool

### 9AT1-E01

- Use to lock the flywheel while removing and replacing the timing belt
- Put it into the teeth of the flywheel to hold the crankshaft up, while releasing or tightening the bolt



Stilo (01-08), Brava / Bravo (95-02)

MODEL: Marea / Weekend (96-03), Multipla (99-09)

**Doblo / Cargo** (02-06)

**ENGINE** 178B3.000, 182A4.000 CODE: 182A6.000, 182B6.000

## **Diesel Engine Setting** Tool (Belt Drive)

#### 9AT2-A01

- The set includes flywheel locking pin, TDC timing pin and tensioner retaining tool
- Use for holding engine timing position when replacing timing belt
- Suitable for Fiat, Iveco, Renault, Citroen / Peugeot, Vauxhall / Opel





#### CONTENTS:

- A TDC timing pin
- B flywheel locking pin (2pc)
- C tensioner retaining tool





2.5D / 2.5DT / 2.8D / 2.8JTD

Croma (93-97) MODEL:

Ducato (87-06) Talento (87-02)

8140.21, 8140.27, 8140.47R **ENGINE** 

8140.43, 8140.438, 8140.63

8144.67

