

# UNIVERSAL

## Camshaft Sprocket Puller

### 9AT3-A04

- Use to hold and remove the camshaft sprocket without damaging the sprocket
- Use with 3/8" square drive tool or 19mm wrench
- Suitable for most sprockets from Ø60 to Ø100 mm



| KT NO.   | Capacity<br>mm |  |  |
|----------|----------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| 9AT3-A04 | 60~100         | 1437                                                                              | 1 / 12                                                                            |



# UNIVERSAL

## Belt Tensioner Lock Pin Set

### 9AT3-B01

- Designed for retaining tensioner plunger in fixed position while replacing timing belt
- Suitable for common vehicle and engine

 17  /  20 / 100



#### CONTENTS :

- 0.79mm / .0310"
- 1.21mm / .0476"
- 1.41mm / .0560"
- 1.51mm / .0594"
- 1.71mm / .0670"
- 1.92mm / .0760"


# UNIVERSAL

## Dial Test Indicator

### 9AT3-F01

- Use to measure and accurately find the piston TDC position
- This tool has to use with TDC Indicator 9AT3-F02
- It can be used for mechanical circularity, flatness.....etc

 63  /  1 / 100



# UNIVERSAL

## TDC Indicator

### 9AT3-F02

- Use to measure if the cylinder piston is at TDC position
- This tool has to use with Dial Test Indicator 9AT3-F01

 292  /  1 / 30

