Pneumatic Grease Pump 20L

9TU11

- The barrel body is made of high-grade steel plate. It can contain 5 gallons(20L) of barrel packed grease from all nations around the world
- Suitable for all sorts of machinery, vehicles, airplanes, ships, etc. The efficient instrument for infusing grease powerfully for lubrication & maintenance purpose
- Pump of separate type: utilize the principle of liquid getting pumped & driven by air compressor to draw in liquid. There are two independent & separate cycle systems of pump out there, which prevents air- compressor-exhaust moisture from getting to the grease inside the barrel and deteriorating its quality



KT NO.	Air Input (bar)	Pressure (PSI)	Pressure Ratio	Grease Ou (bar)	tput Pressure (PSI)	Deliver Rate (cc/sec)	N.W.	G.W.	FJ	CUFT
9TU11-20	4-9	60-130	45 : 1	180-405	2700-5850	30	17	20.5	21.0	6.4

Hand Grease Pump 20L

9TU21

- 20L tank for 5 gallons grease oil
- Suitable for #00,#0,#1,#2 grease oil
- Included 1.8m length hose & pistol sprayer
- 1/4" High pressure 10,000 psi W.P oilfield hose
- Portable equipment with single pull handle
- Suitable for all sorts of machineries, vehicles, airplanes, ships, etc.

Oil Transfer Bucket Pump 20L

9TW21

- Lever pump 20 L tank for oil
- Suitable for diesel fuel, lubricating oils up to SAE 90 and Non-corrosive fluids
- Included 1.8m length hose & sprayer
- Portable equipment with single pull handle



KT NO.	Transmission rate	Hose Length	N.W.	G.W.	CUFT
9TU21-20	4 cc/stroke	1.8 m	8.2 Kg	9.4 Kg	2.2



KT NO.	Deliver Rate	Hose Length	Outlet tube	N.W.	G.W.	CUFT
9TW21-20	65 cc/stroke	1.8m	3/8"	7.8 Kg	8.5Kg	2.2

