
Cordless Butane Hot Air Gun





- Maximum temperature 550°C
- Portable and cordless for convenient application
- Gas control knob for heat adjustment
- Suitable for heat shrink, paint stripping and plastic welding, etc
- Optional 2 nozzle deflectors 6BH21-01 and 6BH21-02 for different operate
- Upright stand for heat shrink and hands free working with our stable and durable stand
- Instant use without needing time to preheat and cool down

▶ Here are some common uses for hot air gun

along with the temperature needed to complete

150~ 200°C	250~ 300°C	350~ 400°C	450~ 500°C		
► Application	► temper	rature	► Distance		
 Shrinking plastic film 	200°C~30	10°C	(5~10cm)		
 Bending plastic pipes 	200°C ~30	10°C	(5~10cm)		
 Softening Adhesives 	300°C ~40	10°C	(1~5cm)		
 Welding plastic 	330°C ~40	10°C	(1~5cm)		
 Stripping paint 	50	10°C	(1cm)		













· Refilling gas

· Adjustable head for 4 angle

 Pull the switch and · Press the ignition button Turn the gas on


KT NO.	Gas Capacity (ml)	Operation Time (min)	Gas Type	Operating Temp °C	Dimension(mm) L x W x H	ŢġŢ	&/ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
6BH21	34	60	Butane	550	168 x 66 x 198	576	1 / 20
6BH21-01	-	-	-	-	-	33	50 / 200
6BH21-02	-	-	-	-	-	21	20 / 200

Cordless Butane Gas Glue Gun



6BJ

- Self-regulating temperature system, avoiding the glue keeping coming out to stuck the nozzle or drip everywhere
- Fast-heating in 1 to 2 Minutes
- Quick and easy to refill gas only 3s, keeps running for approximately 1.5 hours
- Front top heater design for safety usage
- Portable and cordless for convenient application
- Passed the 250 hour continuous work durability test
- Included 2 PC. 11mm glue stick
- Suitable for wood workings, household repairs, artficial flowers, models, art and decorations etc...
- Optional glue stick 6BJ901, pack by 10 PC.
- Ergonomic comfort grip



Gas

Capacity

(ml)

6.8

Refilling gas

KT NO.

6BJ21

6BJ901



Glue size

(mm)

11

11

Gas Type

Butane

 Turn the gas switch on

Operation

Time

(min)

90



Press the ignition button and wait 2-3 min (Make sure the indicator on)

Operating

Temp

160-180







241


140


1 / 10

10

175 x 36 x 155

Ø11 x 150mm





► 6BJ21

