

Transmission Jack

9TY14



- Handle for easy adjustment
- Protection against overloading
- Pedal for hydraulic control
- Telescoping cylinder rams



9TY1421-05A-B



9TY1432-05A-B



9TY1433-05A-B



9TY1434-05A-B

KT NO.	Capacity (T)	Min height (mm)	Max height (mm)	N.W (kg)	G.W (kg)	CUFT
9TY1421-05A-B	0.5	1140	1965	31	35	3.32
9TY1432-03A-B	0.3	1260	1735	31	33	1.69
9TY1433-05A-B	0.5	875	1855	79	88	6.37
9TY1434-05A-B	0.5	870	1795	50	56	3.38
9TYZ1421-05A-B	0.5	1180	1980	29.5	30.5	2.27
9TYZ1431-06A-B	0.6	1270	2075	36.5	37.5	2.93

With single pump 9TY1433-05A-B, 9TYZ1421-05A-B, 9TYZ1431-06A-B

With double pump 9TY1434-05A-B



9TYZ1421-05A-B




9TYZ1431-06A-B


9TY145



- With stronger steel base and nylon wheel



9TY145-004A-B



9TY145-006A-B



9TY145-008A-B



9TY145-015A-B

KT NO.	Capacity (T)	Min height (mm)	Max height (mm)	N.W (kg)	G.W (kg)	CUFT
9TY145-004A-B	0.4	1240	2105	26	29	2.35
9TY145-006A-B	0.6	1135	1980	34	37	3.03
9TY145-008A-B	0.8	850	1840	46	49	2.70
9TY145-015A-B	1.5	1130	1915	56	59	3.05

Pneumatic Transmission Jack

9TY14



KT NO.	Capacity (T)	Min height (mm)	Max height (mm)	N.W (kg)	G.W (kg)	CUFT
9TY1441-05A-B	0.5	850	1815	103	109	6.79
9TY1436-10A-B	1	880	1915	81	90	6.37

With single pump 9TY1436-10A-B, 9TY1441-05A-B



9TY1436-10A-B



9TY1441-05A-B